

43"

55"

65"

75"

86"



KD Series

Floor Standing LED Digital Signage



4K resolution



WIFI/LAN
online transmission



U disk / SD card
offline playback



Remote control
(cloud optional)



Splitting screen



Loop play



7*24 Hours




Android



Multiple sizes

APPLICATIONS



CONTENT MANAGEMENT SYSTEM(CMS)

Cloud-based Content Management



Powerful Functions

- Remote Control (Cloud optional)
- Timer Switch
- Phone Control Option
- Splitting Screen
- Auto Launch
- Loop Play
- In-Time Monitor
- Power-Off Memory
- Sync Play
- Batch Management

iOS and Android Applications

Manage digital signage content on mobile devices



USB Content Playback

Play multiple contents via USB



U disk / SD card
offline playback



SPECIFICATIONS

		KD43V	KD55V	KD65V	KD75V	KD86V
Panel	Display Size(inch)	43''	55''	65''	75''	86''
	Display Scale	9:16				
	Display Dimension(mm)	529.254mm(H)* 940.896mm(W)	680.4mm(H)* 1209.6mm(W)	803.52mm(H)* 1428.48mm(W)	927.936mm(H)* 1649.66 mm(W)	1053mm(H)* 1872mm(W)
	Touch	IR Touch with 20 points/ Non-Touch(optional)				
	Respond Time(ms)	8 ms				
	Contract	≥1200:1				≥3000:1
	Visual Angle	178°/178°				
	Display Color	16.7M (8-bit)				
	Resolution	1080 * 1920			3840 * 2160	
	Brightness(cd/m2)	450 cd/m²				
	Back Light	WLED				
	speaker	8Ω 5W*2				
	Lifespan	60000 h				
Motherboard	Type	Android				
	CPU	T972, RK3568(optional)				
	ROM	2GB/4GB(Optional)				
	SSD/HDD	16GB/32GB(optional)				
	Operation System	Android 9/11(optional)				
Language	Multi-languages	English, Chinese, Spanish,etc				
Ports	Video Port	HDMI out*1, T972 supports HDMI input			HDMI in*1, AV in*1, AV out*1	
	Audio Port	1				
	USB Port	USB*2				
	TF Card Slot	1				
	SIM Card Slot	1(need work with 4G modem)				
	Communication Port	RJ45*1 (10M/100M/1000M)				
Network	LAN(RJ45)	10/100/1000 Mbp				
	WIFI/Bluetooth	IEEE 802.11b/g/n				
		Bluetooth (optional)				
	4G Modem	(optional)				
Power	Input	AC 100-240 V ~ 50/60 Hz				
	Max Power Consumption	≤85W	≤110W	≤160W	≤245W	≤420W
Package	Carton box(mm)	1890mm* 180 mm* 760 mm	2010mm* 180 mm* 930 mm	1990mm* 180 mm* 1040 mm	2120mm*225 mm* 1145mm	2240mm*225 mm* 1310 mm
	Net weight(kg)	Around 50kg	Around55kg	Around 82kg	Around100kg	Around120kg
Working Temperature	Working Time(h)	7*24h				
	Working Temperature	0℃~+50℃				
	Working Humidity	10%RH ~ 85%RH				
	Storage Humidity	0℃~+60 ℃				
Installation	/	Floor standing				
	Installation Direction	Vertical				
Others	Color	Black, White				
	Surface Tempered Glass	3mm				

